



# FILL-LITE®

The soft light company

[www.fill-lite.com](http://www.fill-lite.com)



## Fill-Lite 200

The Fill-Lite 200 is the lighting breakthrough for gaffers and DP's in the digital era and an excellent soft light for location or studio use with low power requirements.

Fill-Lite 200 is our most portable model, excellent for film shoots, HD video, or still photography. It incorporates a single square light source on a yoke and all electronics onboard. The onboard electronics include manual dimming and daisy chaining to link fixtures, universal AC power input, and ports for optional battery and DMX 512 for studio use (wired or wireless).

Standard with all Fill-Lite fixtures, the LED's are selected for color and performance consistency making this light the softest, most natural light source on the market today.

### FEATURES

- Clean design
- Wrap around soft light
- Amazingly thin profile when mounted
- All-in-one fixture. No setup, just plug it in!
- Very low power requirement
- No heat from fixture. Excellent on talent, table-top, or tight sets
- Control panel mounted on yoke for easy operation

### ACCESSORIES

- Soft egg crate 40° / 50° (SnapGrid™ SFF0202)
- Custom soft case
- Custom flight case
- DMX512 module plugin, field installed
- DMX over WiFi module plugin, field installed
- 24-36VDC Battery Inverter module plugin, field installed

# SPECIFICATIONS

## OPTICS

	DAYLIGHT	TUNGSTEN
TLCI	95	93
lux @3'	1483	1360

Beam Angle: 114°

LED Life: 50,000 hours

## MECHANICAL DESIGN

- Description: Yoke mounted ultra-soft 24" (61cm) light square with custom designed solid state electronics
- Yoke uses a combination of powder coated and anodized steel and aluminum
- Onboard manual dimmer 10-100%
- 3.5mm 3-conductor (stereo) link cable connection
- Convection cooling, silent
- Minimum/Maximum ambient operating temp: -10C to +40C
- Yoke accepts multiple customizing plug-in modules

## DIMENSIONS

- Fixture: 28"w x 30.5"h x 2"d  
(71cm x 77.5cm x 5cm)

## WEIGHT

- Fixture: 21lbs (9.5kg)

## POWER

Input AC power: Universal 90-250 VAC

- Power consumption: 57W
  - Fused protection: 1A 250V Fast
- Input DC Power: 24-36 VDC @2-3A
- Connection: 3-pin XLR  
(pin # 1 - / pin #2 + / pin #3 NC)

## CERTIFICATIONS

- RoHs compliant
-  

## WARRANTY

- 1 year parts and labor

## PACKAGE INCLUDES

- Gel clips, mounted
- Baby female receiver
- Yoke with built-in power supply
- Detachable US power cord (3-prong)